



Parameters of the Crystal 产品参数性能

	Series 系列	CXB5 系列
1	Nominal Frequency 标称频率	8.0000M~50.0000MHz
2	Holding 封装形式	SMD 5032 GLASS
3	Vibration Mode 振动模式	AT CUT FUND AT 切 基波
4	Frequency Tolerance @ 25±3℃ 调整频差	±10PPM ±15PPM ±20PPM
5	Frequency Stability@ -40℃~+85℃ 工作温度条件下的频率容差	±20PPM ±30PPM ±50PPM
6	Operating Temperature Range 工作温度	-20℃~+70℃ -40℃~+85℃
7	Store Temperature Range 存储温度	-55℃~+125℃
8	Equivalency Resistance 等效电阻	30 Ω ~120 Ω
9	Load Capacitance 负载电容	8PF 12PF 20PF or Specify
10	Load Capacitance 静态电容 C0	5.0PF~7.0PF
11	Drive Level 激励功率	100~300 μ W(100 μ W Typical)
12	Insulation Resistance 绝缘阻抗	>500MΩ at DC 100V±15V
13	Aging 老化	±3PPM/Year
14	Marking 打标	XDL **, ****M
15	Packing Unit 包装单位	1000pcs/Reel



Outline drawing 外观尺寸

单位: mm

